

Features


- High Blocking Voltage with Low On-Resistance
- High Speed Switching with Low Capacitances
- Avalanche Ruggednes

Product Summary

V_{DS}	1200V
$R_{DS(on)_{typ}}$	160mΩ
I_D	17A

Applications

- Solar Inverters
- Switch Mode Power Supplies
- High Voltage DC-DC Converters
- Battery Chargers



Package Marking and Ordering Information

Part #	Marking	Package
T1M160120K	1M160120K	TO-247-4

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	1200	V
Continuous drain current $T_C = 25^\circ\text{C}$, $V_{GS} = 18\text{V}$ $T_C = 100^\circ\text{C}$, $V_{GS} = 18\text{V}$	I_D	17 12	A
Pulsed drain current ($T_C = 25^\circ\text{C}$, t_p limited by T_{jmax})	$I_{D \text{ pulse}}$	34	A
Gate-Source voltage	V_{GS}	-4/+18	V
Gate-Source voltage (Absolute maximum values)	V_{GSmax}	-8/+22	V
Power dissipation ($T_C = 25^\circ\text{C}$)	P_{tot}	116	W
Operating junction and storage temperature	T_j, T_{stg}	-55...+175	$^\circ\text{C}$

- Example of acceptable V_{GS} waveform



Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal resistance, junction – case. Max	R_{thJC}	1.29	°C/W
Thermal resistance, junction – ambient. Max	R_{thJA}	40	

Electrical Characteristic (at $T_j = 25\text{ °C}$, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		

Static Characteristic

Drain-source breakdown voltage	BV_{DSS}	1200	-	-	V	$V_{GS}=0V, I_D=100\mu A$
Gate threshold voltage	$V_{GS(th)}$	2	3.1	4	V	$V_{DS}=V_{GS}, I_D=2.3mA$
Zero gate voltage drain current	I_{DSS}	-	1	20	μA	$V_{DS}=1200V, V_{GS}=0V$ $T_C=25\text{ °C}$
		-	5	-		$T_C=175\text{ °C}$
Gate-source leakage current	I_{GSS}	-		100	nA	$V_{GS}=18V, V_{DS}=0V$
Drain-source on-state resistance	$R_{DS(on)}$	-	160	208	m Ω	$V_{GS}=18V, I_D=8A,$ $T_j=25\text{ °C}$
		-	250	-		$T_J=175\text{ °C}$
Transconductance	g_{fs}	-	5	-	S	$V_{DS}=20V, I_D=8A$

Dynamic Characteristic

Input Capacitance	C _{iss}	-	624	-	pF	V _{DS} = 1000V V _{GS} = 0V T _J = 25°C V _{AC} = 25mV f = 1MHz
Output Capacitance	C _{oss}	-	42	-		
Reverse Transfer Capacitance	C _{rss}	-	6	-		
Gate Total Charge	Q _G	-	37.4	-	nC	V _{DS} = 800V V _{GS} = 0/18V I _D = 8A I _G = 10mA
Gate-Source charge	Q _{gs}	-	5.3	-		
Gate-Drain charge	Q _{gd}	-	20.6	-		
Turn-On Switching Energy	E _{ON}	-	11	-	μJ	V _{DD} =800V, V _{GS} =-4/18V R _G =5Ω, I _D =8A Inductive Load, T _J =25°C
Turn-Off Switching Energy	E _{OFF}	-	230	-		
Turn-on delay time	t _{d(on)}	-	12.25	-	ns	
Rise time	t _r	-	18.68	-		
Turn-off delay time	t _{d(off)}	-	17.37	-		
Fall time	t _f	-	11.82	-		
Gate resistance	R _G	-	3.3	-	Ω	V _{AC} = 25mV, f=1MHz

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}		3.6		V	$V_{GS} = 0V, I_{SD} = 4A,$ $T_J = 25^\circ C$
			3.2			$V_{GS} = 0V, I_{SD} = 4A,$ $T_J = 175^\circ C$
Body Diode Reverse Recovery Time	t_{rr}	-	13.5	-	ns	$V_R = 800V, V_{GS} = 0V$ $I_D = 8A$ $di/dt = 800A/\mu S$ $T_J = 25^\circ C$
Body Diode Reverse Recovery Charge	Q_{rr}	-	36.8	-	nC	

Typical Performance Characteristics

Fig 1. Output Characteristic (T_J=-55°C)




Fig 2. Output Characteristic (T_J=25°C)




Fig 3. Output Characteristic (T_J=175°C)




Fig 4: R_{ds(on)} Vs I_{ds} Characteristic




Fig 5: R_{ds(on)} vs. Temperature




Fig 6: Transfer Characteristic




Fig 7: Body-diode Characteristic ($T_J=-55^{\circ}\text{C}$)




Fig 8: Body-diode Characteristic ($T_J=25^{\circ}\text{C}$)




Fig 9: Body-diode Characteristic ($T_J=175^{\circ}\text{C}$)




Fig 10: V_{TH} Vs T_J Temperature Characteristic




Fig 11: Gate Charge Characteristics




Fig 12: 3rd Quadrant Characteristic($T_J=-55^{\circ}\text{C}$)




Fig 13: 3rd Quadrant Characteristic($T_J=25^{\circ}\text{C}$)




Fig 14: 3rd Quadrant Characteristic($T_J=175^{\circ}\text{C}$)




Fig 15: Capacitance Characteristic




Fig 16: Safe Operating Area





Fig 17: Transient Thermal Impedance



Test Circuit & Waveform

Figure A. Definition of switching times

Figure B. Dynamic test circuit




Figure C. Definition of body diodeswitching characteristics





Figure C. Definition of diode switching characteristics

Package Outline:



Contact Information

TANI website: <http://www.tanisemi.com> Email: tani@tanisemi.com
For additional information, please contact your local Sales Representative.

 ® is registered trademarks of TANI Corporation.

Product Specification Statement

The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. TANI shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and TANI assumes no responsibility for the application of the product. TANI strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, TANI cannot guarantee that the information provided in the product specification is entirely accurate and error-free. TANI shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications.

TANI reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with TANI to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult TANI in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.

The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. TANI shall assume no responsibility for any consequences resulting from such usage.

Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. TANI shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.